

halfords

Bike Trailer – Stroller Kit Accessory Owner's Manual

Please keep this Owner's Manual for future reference.

PRIOR TO ASSEMBLY

Please read this Owner's Manual completely before assembling or operating this product.

This product should be assembled by an adult.

Installing Optional Stroller Kit.

Your trailer can be fitted with an optional stroller kit for convenient conversion from trailer to stroller when circumstances require. Trailering your child to the destination of your choice is great, but having the convenience of a stroller when you reach your destination expands your options. Head to the park or the seashore, then quickly convert to stroller function for shopping, hiking or a walk along the seashore. Conversion takes but a moment, and the comfortable handlebar, short wheelbase and swivel wheel makes pushing your child smooth and easy. Of course, the 5 point harness is still there to secure your child in the stroller.

The Stroller Conversion Kit includes:



1. Handlebar
2. Handlebar mounting brackets and hardware
3. Hex key and spanner
4. Safety Wrist strap
5. Front Swivel Wheel/Fork assembly
6. Swivel wheel mounting bracket and Hardware
7. QR pin with strap

halfords

STEP 1 – Assemble the Swivel Wheel Mounting Bracket

Place the frame of the assembled trailer on the rear frame, with front of trailer facing up.



Unsnap the fabric from around the front crossbar



Locate the stroller wheel mounting hole in the center of the front frame tube.

halfords



Slide wheel bracket over the frame, allowing the locator pin to fit in the small hole in the front face of the frame tube. Make certain that that threaded nut side of the bracket is on top. The clean hole in the bracket will face the bottom.



halfords

Insert the threaded fixing knob through the hole in the bottom of the bracket, and tighten securely



Wrap the strap of the QR pin around the frame, and back through the loop in the strap to fix it to the frame.



Re-attach the lower trailer fabric to the front frame, wrapping it, securing the snaps.



halfords

Insert the axle of the swivel wheel in the bracket and then insert the QR pin through the hole in the bracket, snapping the QR pin closed to lock the wheel in place.



STEP 2 – Assemble the Handlebar Mounting Brackets

Note: The stroller kit handlebar is compatible with both the single and double child trailer models. Please follow the instructions below to ensure you assemble the mounting brackets correctly for your trailer.

Single Trailer Mounting

Locate the hole in the trailer rear frame tube

Take one of the mounting clamps and loosen the black hand knob until the clamp can fit over the frame tube. Position this clamp on the tube so the thru-hole aligns with the hole in the frame. The open side of the clamp should be facing **out**, as shown below, with the single hole facing the rear of the trailer.

halfords

Insert one of the screws provided from front to rear through the clamp and tube, and tighten snug with the hex wrench and spanner provided.

Follow the same procedure on the opposite side of the trailer



Loosen hand knob and Insert handlebar in both sides of clamp simultaneously. The spring pins may be pressed by your finger to allow them to align with the hole in the clamp. When the spring pins on both sides are aligned with the holes in the clamp, tighten the hand knob to secure the handlebar.

halfords

Double Trailer Mounting

Locate the hole in the trailer rear frame tube

Take one of the mounting clamps and loosen the black hand knob until the clamp can fit over the frame tube. Position this clamp on the tube so the thru-hole aligns with the hole in the frame. The open side of the clamp should be facing **in**, as shown below, with the single hole facing the rear of the trailer.

Insert one of the screws provided from front to rear through the clamp and tube, and tighten snug with the hex wrench and spanner provided. (As shown above)



Follow the same procedure on opposite side of the trailer.

Loosen hand knob and Insert handlebar in both sides of clamp simultaneously. The spring pins may be pressed by your finger to allow them to align with the hole in the clamp. When the spring pins on both sides are aligned with the holes in the clamp, tighten the hand knob to secure the handlebar.

halfords

NOTE: When preparing for installation of the stroller handlebar, please make sure you assemble correctly for single child or double child models. See pictures below for guidance:



Single Child Configuration
Handlebar to **Outside** of frame



Double Child Configuration
Handlebar to **Inside** of frame

Before starting out, loop the included wrist strap around the handlebar as shown. Always use the safety wrist strap when pushing your child in the stroller. This feature allows you to remain in control of the trailer in the event of a fall or sudden distraction.



halfords

Using the Optional Stroller Kit

Once installed, the conversion from trailer to stroller takes but a few seconds. First release the trailer arm by removing the QR pin holding it in place. Fold the arm back under the trailer, then refit the pin to hold the arm in place under the frame.

Next, insert the front wheel in the bracket on the front frame, secure the QR pin, and the wheel is ready.

Next install the handlebar as described above, and you are ready to go.

The handlebar can remain on the trailer, if you prefer, when being towed by a bicycle.

Always use parking brake when loading or unloading stroller

Never leave child unattended.

Always use safety harness.

Warranty Service: Please return product to store or contact:

Halfords Customer Services Department,
Halfords Group plc, Washford West,
Redditch,
Worcestershire,
B98 0DE
(+44) 0345 504 53 53
customer.services@halfords.co.uk